Notices to Airmen Sunbelt Ag Expo

SUNBELT AG EXPO

MOULTRIE, GA October 15–17, 2019

SPECIAL AIR TRAFFIC PROCEDURES

The following procedures are in effect to enhance safety and minimize delays at Spence Airport (KMUL) Moultrie, GA during the Sunbelt Ag Expo.

Two-way radio communication with ATC is required.

Be alert for a high volume of high performance and other types of traffic including banner tow, advertising, and law enforcement aircraft.

Pilots are encouraged to keep transmissions to a minimum and listen to the ATIS.

Expect possible delays due to traffic volume.

All flight crews should be familiar with VFR arrival procedures for MUL.

OBTAIN A COMPLETE WEATHER BRIEFING AND CHECK NOTAMS PRIOR TO DEPARTURE TO ENSURE YOU HAVE THE MOST CURRENT INFORMATION.

TEMPORARY AIRPORT TRAFFIC CONTROL TOWER

The FAA will operate a Temporary Airport Traffic Control Tower at Spence Airport (KMUL).

FREQUENCIES	
ATIS	118.65
GROUND	121.6
TOWER	127.4

HOURS OF OPERATION: 0800-1800 EDT (1200-2200 UTC) daily.

APPROACH CONTROL

Valdosta Approach will provide Approach Control Service on frequency 132.37 for arriving and departing IFR aircraft and VFR aircraft requesting traffic advisories.

ARRIVALS

VFR

To minimize frequency congestion, keep transmissions to a minimum; report call sign, aircraft type, and position.

Monitor ATIS for wind, altimeter, and arrival information.

GEORGIA 3-SPORT-25

Sunbelt Ag Expo Notices to Airmen

From the South/Southwest: Proceed over the Moultrie Municipal Airport (MGR), remain at or above 1800 feet MSL to stay clear of the MGR traffic pattern, then contact Spence Tower.

From the Northwest/North/East: Contact Spence Tower five (5) miles from MUL. Expect to enter a RIGHT downwind to RWY 32 or LEFT downwind to RWY 14, unless otherwise instructed by ATC.

DO NOT over-fly the Exposition below an altitude of 1300FT MSL.

IFR

There are NO published IAPs for Spence Airport.

When weather conditions require instrument approaches, the IAPs for MGR Airport are the most expeditious.

After canceling IFR with Valdosta Approach, pilots may continue VFR to MUL if weather conditions permit.

DEPARTURES

VFR

Monitor ATIS (118.65) for runway and taxi information.

MONITOR Ground Control (121.6), TAXI to the red or blue barrels for departure (red barrels intersection departure), and HOLD SHORT of the runway.

When number one in line, contact Tower (127.4), and advise ATC of direction of flight.

MONITOR ground control - DO NOT contact Tower until number one in line.

IFR

File flight plans a minimum of one hour prior to the proposed departure time.

If weather conditions permit, pilots should request IFR clearances after they are airborne with Valdosta Departure Control (frequency 132.37).

Spence Ground Control (frequency 121.6) will issue IFR clearances on request. Pilots should expect departure delays.

All aircraft expect an initial maximum altitude of 7000FT until clear of the Moody1 MOA.

LEIDOS FLIGHT SERVICE

Pilot briefing and flight planning services are available online through Leidos Pilot Portal at https://www.1800wxbrief.com/Website/ or by telephone at 1–800–WX–BRIEF (1–800–992–7433). Press 1 for a briefer, then press 4–2–1 or say "Georgia".

3-SPORT-26 GEORGIA